



[www.tysol.com](http://www.tysol.com)

## Tysol-78L

**Chemistry designed for spray conveyors, cabinets and automatic wash systems. Formulated to attack dirt, oil, lubricants and heavy grease.**

**Tysol-78L** is a premium liquid alkaline, foam controlled detergent for use in spray conveyors, cabinets and automatic wash systems for cleaning all types of parts. The product is non-hazardous and biodegradable.

- Safe on multiple metal surfaces including aluminum and alloys.
- Safe on most painted surfaces, plastic or rubber parts.
- Attacks and destroys carbon, heavy grease, lube oil and soils.
- Built in water conditioning and flash rust inhibitors.
- Controls foam build up at warm operating temperatures above 135° F.
- Generally safe for disposal to sewage treatment facilities.

### USE INSTRUCTIONS:

**Tysol – 78L** can be used at 2 to 5 ounces per 1 gallon of hot water. Close the cabinet door completely, activate pump for about three minutes to disperse the cleaner. Concentration of the product can be monitored by the use of an alkalinity titration kit. The temperature range recommended for cleaning is 135° to 190° F, typically for 5 to 30 minutes. The wash solution is free rinsing resulting in no residue when rinsed properly.

### TECHNICAL DATA:

pH (use dilution).....	Approximately 12
Color.....	Amber
Rinseability.....	Excellent
VOC.....	None